T1S R1WDUCHESNE COUNTY MONUMENT SURVEY RECORD 5/8"X24" REBAR WITH A 2½" BRASS DUCHESNE COUNTY SEC 7 SEC 8 MONUMENT AT SECTION CORNER 1/4 U.S.B.&M. 2638. 16 T-55'02" NAIL AND WASHER IN LEFT SIDE OF RR TIE FENCE CORNER 8 N 84°28'38" E LEFT SIDE OF RR TIE FENCE CORNER N 6. 33.9-24.49' N 85°44'03" E "x" CHISELED IN TOP OF PIPE FENCE CORNER O= "X" CHISELED IN DUCHESNE COUNTY TOP OF PIPE 2½ DIA. ALUMINUM 2½ DIA. ALUMINUM PIPE AND CAP MONUMENT AT 1/4 FENCE CORNER CORNER 00°17'53" NORTH NOTE: THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED FROM G.P.S. OBSERVATIONS AT A CONTROL POINT (SECTION CORNER) LOCATED AT LAT. 40"23"20.57790"N AND LONG. 110"01"46.98583"W USING THE UTAH STATE G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK MAINTAINED AND OPERATED BY THE AUTOMATED GEOGRAPHIC REFERENCE CENTER SCALE: 1"=30' 5/8"X24" REBAR WITH A 2½" BRASS DUCHESNE COUNTY MONUMENT AT SECTION CORNER *30'*

DESCRIPTION OF CORNER EVIDENCE FOUND

FOUND A BENT PIPE MONUMENT WITH THE CAP BROKEN OFF AT THE POSITION OF THE 1/4 CORNER

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THE CORNER

SET A ALUMINUM DUCHESNE COUNTY PIPE MONUMENT AT THE POSITION OF THE 1/4 CORNER AFTER ROAD CONSTRUCTION



STATE PLANE COORDINATE DATA

(U.S. SURVEY FEET)

NAD83 UTAH CENTRAL ZONE
N: 7321722.212
E: 2049788.249

NAVD88 EL: 5836.98'

LATITUDE: 40°24'38.79808" N **LONGITUDE:** 110°01'47.35907" W

ELLIPSOID HEIGHT: (GEOID 03 CONUS)

PUBLIC LAND SURVEY SYSTEM GCDB ID NO.

5782.90'

UT300010S0010W0_200540

CERTIFICATION

I <u>Jerry D. Allred</u>, Professional Land Surveyor, State of Utah, do hereby certify that I have performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve same

Date <u>28 FEB 2018</u>

Jerry D. Allred, Professional Land Surveyor Certificate No. 148951 Duchesne County Surveyor

